

SAFETY DATA SHEET

1. Identification

Product identifier FNR5 Automatic Transmission Fluid

Other means of identification

FIR No. 175125

Recommended use Automatic Transmission Fluid

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company Name Ford Motor Company

Address Attention: MSDS Information, P.O. Box 1899

Dearborn, Michigan 48121

USA

 Telephone
 1-800-392-3673

 MSDS Information
 1-800-448-2063

msds@brownart.com

Emergency telephone

numbers

Poison Control Center: USA and Canada: 1-800-959-3673 INFOTRAC (Transportation): USA and Canada 1-800-535-5053

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

May irritate eyes and skin. May cause irritation of respiratory tract.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
White mineral oil (petroleum)		8042-47-5	10 - < 20
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	5 - < 10
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	3 - < 5
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	3 - < 5

FIR No.: 175125 SDS US

Issue Date: 06-22-2015

Version: 01 1 / 7

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), solvent-dewaxed light paraffinic		64742-56-9	3 - < 5
Distillates (petroleum), solvent-refined light paraffinic		64741-89-5	3 - < 5

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if Eve contact

irritation develops and persists. Rinse with water.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

Direct contact with eyes may cause temporary irritation.

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Methods and materials for containment and cleaning up In case of spills, beware of slippery floors and surfaces. Keep unnecessary personnel away. Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapors. For personal protection, see section 8 of the SDS.

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Avoid prolonged exposure. Use only in well-ventilated areas. See Section 8 of the SDS for Personal Protective Equipment.

Conditions for safe storage, including any incompatibilities Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

FIR No.: 175125 SDS US 2/7 Version: 01

Issue Date: 06-22-2015

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Conta Components	aminants (29 CFR 1910.1000) Type	Value	Form		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.		
,		2000 mg/m3 500 ppm			
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	PEL	5 mg/m3	Mist.		
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	PEL	5 mg/m3	Mist.		
		2000 mg/m3 500 ppm			
Distillates (petroleum), solvent-refined light paraffinic (CAS 64741-89-5)	PEL	5 mg/m3	Mist.		
White mineral oil (petroleum) (CAS 8042-47-5)	PEL	5 mg/m3	Mist.		
US. ACGIH Threshold Limit Values Components	Туре	Value	Form		
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.		
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.		
Distillates (petroleum), solvent-refined light paraffinic (CAS 64741-89-5)	TWA	5 mg/m3	Inhalable fraction.		
White mineral oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.		
US. NIOSH: Pocket Guide to Chemical Hazards					
Components	Туре	Value	Form		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.		
	TWA	5 mg/m3	Mist.		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	STEL	10 mg/m3	Mist.		
,	TWA	5 mg/m3	Mist.		
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.		
,	TWA	5 mg/m3	Mist.		
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	STEL	10 mg/m3	Mist.		
	TWA	5 mg/m3	Mist.		
Distillates (petroleum), solvent-refined light paraffinic (CAS 64741-89-5)	STEL	10 mg/m3	Mist.		
	TWA	5 mg/m3	Mist.		

FIR No.: 175125 SDS US

Version: 01 Issue Date: 06-22-2015 **US. NIOSH: Pocket Guide to Chemical Hazards**

Form Value Components Type White mineral oil STEL 10 mg/m3 Mist. (petroleum) (CAS

8042-47-5)

TWA 5 mg/m3 Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s). Appropriate engineering

controls

Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

The choice of an appropriate glove does not only depend on its material but also on other quality Hand protection

> features and is different from one producer to the other. Suitable chemical protective gloves should be worn when the potential exists for prolonged or repeated skin exposure. Neoprene gloves are

recommended. Nitrile or butyl rubber gloves are recommended.

Other Wear suitable protective clothing. Wear appropriate chemical resistant clothing if applicable.

If engineering controls do not maintain airborne concentrations to a level which is adequate to Respiratory protection

protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection

Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Lubricant. **Form** Color Red. Mild. Odor

Not available. **Odor threshold** Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

345.2 °F (174.0 °C) COC Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Not available. Vapor density

0.85 Relative density

Relative density temperature 59 °F (15 °C)

Solubility(ies)

Version: 01

INSOLUBLE Solubility (water)

FIR No.: 175125 SDS US

Issue Date: 06-22-2015

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

35.77 cSt Kinematic viscosity 104 °F (40 °C) Kinematic viscosity

temperature

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons. Oxides of phosphorus. Sulfur oxides. Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Inhalation

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Skin contact

Direct contact with eyes may cause temporary irritation. Eve contact

May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

May irritate eyes and skin. May cause respiratory irritation. **Acute toxicity**

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eve damage/eve

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Base oil

severely refined: Not carcinogenic in animal studies. Representative material passes IP-346,

Modified Ames test, and/or other screening tests.

IARC Monographs. Overall Evaluation of Carcinogenicity

White mineral oil (petroleum) (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

FIR No.: 175125 SDS US

Issue Date: 06-22-2015

Version: 01

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of this product.

bloaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Don't pollute. Conserve resources. Return used oil to collection centers. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

<Unspecified>

Not regulated as dangerous goods.

IATA

<Unspecified>

Not regulated as dangerous goods.

IMDG

<Unspecified>

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Not established.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

Version: 01

FIR No.: 175125 SDS US

Issue Date: 06-22-2015

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9) Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4) Distillates (petroleum), solvent-refined light paraffinic (CAS 64741-89-5)

White mineral oil (petroleum) (CAS 8042-47-5) US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9) Distillates (petroleum), solvent-refined light paraffinic (CAS 64741-89-5) White mineral oil (petroleum) (CAS 8042-47-5)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

06-22-2015 Issue date

Version # 01

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0

Health: 1 NFPA ratings

Flammability: 1 Instability: 0

Preparation Information and

Disclaimer

This document was prepared by FCSD-Toxicology, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical quidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

XT-9-QMM5 Part number(s)

FIR No.: 175125 SDS US

7/7 Version: 01